

Model: 1-inch Non-Metallic

Performance Specifications: 1" Non-Metallic

Ratio	1:1
Maximum GPM (LPM):	53.0 (200.6)
Displacement Gallons Per Cycle (Liters):	0.232 (.88)
Air Inlet:	1/4 - 18 NPTF
Fluid Inlet:	ANSI / DIN Flange (Side Or Center) 1-11-1/2" Nptf-1, Rp 1-11 Bs Threads
Fluid Outlet:	ANSI / DIN Flange (Side Or Center) 1-11-1/2" Nptf-1, Rp 1-11 Bs Threads
Maximum Operating Pressure PSI (bar):	120 (8.3)
Suspended Solids Maximum DIA IN. (mm):	1/8" (3.2)
Weight - LBS. (Kg):	19.35 (8.78) Polypropylene, Threaded Ports 19.59 (8.89) Polypropylene, Center Ported 19.87 (9.01) Polypropylene, Side Ported 25.83 (11.72) Kynar® (P.V.D.F.), Threaded Ports 26.72 (12.12) Kynar® (P.V.D.F.), Center Ported 27.15 (12.32) Kynar® (P.V.D.F.), Side Ports
Maximum Dry Suction Lift:	19 Ft. (Elastomer Fitted)

