

Model: 1½" Metallic

**Performance Specifications: 1 1/2" Metallic**

<b>Ratio</b>	1:1
<b>Maximum GPM (LPM):</b>	123 (465)
<b>Displacement Gallons Per Cycle (Liters):</b>	.588 (2.23)
<b>Air Inlet:</b>	1/2 - 14 NPTF-1
<b>Fluid Inlet:</b>	1 1/2" - 11-1/2 NPTF, 1 1/2 -11 BSP, 1 1/2" ANSI/DIN Flange
<b>Fluid Outlet:</b>	1 1/2" - 11-1/2 NPTF, 1 1/2 -11 1 1/2" ANSI/DIN Flange
<b>Maximum Operating Pressure PSI (bar):</b>	120 (8.3)
<b>Suspended Solids Maximum DIA IN. (mm):</b>	1/4-inch (6.4)
<b>Weight - LBS. (Kg):</b>	33.9 (15.4) PX15R-XAX-XXX 61.2 (27.8) PX15R-XSX-XXX 73.2 (33.2) PX15R-XCX-XXX 86.9 (39.4) PX15R-XHX-XXX add 1.6-lbs (0.73-kg) for aluminum air motor add 17.6-lbs (8.0-kg) for stainless steel air motor
<b>Maximum Dry Suction Lift (m):</b>	14 ft. (4.2) Elastomer fitted

